



## MARSTON *free* Universal-Dichtung

Januar 20

Permanently plastic, very adhesive sealant. Due to its excellent thermal, mechanical and chemical resistance, is MARSTON free universal sealant particularly suitable for demanding and critical sealing compounds.

### No isocyanates! No dangerous good!

Base	Polyurethan
Appearance	green
Density (25°C)	1,10 g/cm <sup>3</sup>
Max. gap filling	approx. 0,25 mm
Consistency	pasty
Flash off time	none
Temperature resistance	-55°C to +200°C
Storage stability at room temperature Compressed air cartridge tube 85 g, cartridge 330 g	24 months 5 years

### Resistance

MARSTON Universal sealing is resistant to all mineral oils and a variety of synthetic oils, to lubricants, fuels, additives, air, gases, water and water-antifreeze mixtures.

### Areas of application

The automotive and motorcycle industries, tractor industry, engine and electrical industries, turbines and nuclear power stations, machine and transmission construction, the foodstuffs industry, mining, chemical and petrochemical industries, gas, water and electricity works etc.

### Instruction for use

Clean the sealing surfaces with MARSTON Cleaner. Apply a thin film of MARSTON Universal seal onto one or both sides. Then Assemble. Due to the nature of the compound tightening of assembled components may be needed. No longer waiting time required!

The values are average values. They serve merely for your information, but assume no warranty.

Bergheimer Str. 15 | D-53909 Zülpich | Tel. 02252/94150 | [info@marston-domsel.de](mailto:info@marston-domsel.de)  
[www.marston-domsel.de](http://www.marston-domsel.de)



Properties	
<ul style="list-style-type: none"> <li>○ Contains no solvents</li> <li>○ Contains no isocyanates</li> <li>○ Not dangerous</li> <li>○ Without Hazardous Substances</li> <li>○ Permanently plastic</li> <li>○ Excellent adhesion on sealing surfaces</li> </ul>	<ul style="list-style-type: none"> <li>○ Immediately usable</li> <li>○ Resistant to many media</li> <li>○ Easy dismantling</li> <li>○ Remains plastic, no cracking</li> <li>○ No flash-off required</li> </ul>
Packaging	Item number
6 x tubes à 80 g	MMD.F.T85
12 x Dura-Press à 200 g Automatic cartridge	MMD.F.K200
20 x cartridge à 330 g	MMD.F.K300
12 x compressed air cartridge	MMD.F.DL200

Bergheimer Str. 15 | D-53909 Zülpich | Tel. 02252/94150 | [info@marston-domsel.de](mailto:info@marston-domsel.de)  
[www.marston-domsel.de](http://www.marston-domsel.de)