

## PRODUCT DESCRIPTION

Loctite® 3D 3820™ is a clear light-curing acrylic resin that may be used for functional prototyping via stereo-lithography. Loctite® 3D 3820™ cures with very short exposure to monochromatic light sources such as LED or Laser. Printed articles made from Loctite® 3D 3820™ exhibit good print resolution and high optical clarity. Loctite® 3D 3820™ is a low viscosity liquid that is printable at room temperature across various Laser SLA and DLP Platforms.

<b>Technology</b>	Stereolithography Resin
Appearance	Clear liquid <sup>LMS</sup>
Chemical Type	Acrylic
Odor	Mild
<b>Cure</b>	Ultraviolet (UV)/ Visible light
Viscosity	Low
<b>Application</b>	Functional Prototyping
Specific Benefits	<ul style="list-style-type: none"> <li>• Good print resolution</li> <li>• Short exposure times</li> <li>• High clarity</li> </ul>

## TYPICAL PROPERTIES OF UNCURED MATERIAL

Specific Gravity g/cm<sup>3</sup> @ 25°C 1.1<sup>LMS</sup>

Flash Point - See MSDS

Viscosity, Cone & Plate, mPa\*s (cP):  
 Temperature: 25C, Shear Rate: 200 s<sup>-1</sup> 800-1000<sup>LMS</sup>

## TYPICAL CURING PERFORMANCE

Loctite® 3D 3820™ can be cured by exposure to UV and Visible light of sufficient intensity and wavelength. Cure rate and ultimate depth of cure depend on light intensity, spectral distribution of the light source, exposure time and light transmittance of the printer window through which the light must pass. Loctite® 3D 3820™ will cure with DLP and Lasers ranging from 300-450nm.

The following working curve values were determined using a Loctite PR10 DLP printer at 405nm wavelength;

Measurement	Unit	Value
Critical Exposure (E <sub>c</sub> )	mJ/cm <sup>2</sup>	24.3
Penetration Depth (D <sub>p</sub> )	mm	0.246

## TYPICAL PROPERTIES OF CURED MATERIAL

Samples prepared at 0.050 mm layer thickness on LOCTITE PR10 DLP printer using recommended exposure settings. Samples were exposed to additional light after removal from the print head; 100 seconds per side @ 100% intensity using Loctite CL36 cure chamber.

All data is recorded on specimens printed in the XY plane. Some variation is expected when printing in Z plane. Contact your local Loctite Technical Service team for further information.

## Physical Properties:

Shore Hardness, ASTM D2240, Durometer D 60  
 Volume Shrinkage, % 7.5  
 Linear Shrinkage, ASTM D792, % 2.6

Physical Property	Unit	As Printed	Final
Elongation, at break, ASTM D638	%	45-49	27-47
Tensile Strength, ASTM D638	MPa	17-19	18-28
	ksi	2.5-2.8	2.6-4.1
Tensile Modulus, (Secant 0.002), ASTM D638	MPa	370-450	900-1100
	ksi	54-65	131-159
Notched IZOD impact ASTM D256	J/m	33-40	31-37

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Safety Data Sheet (SDS).**

## Directions for use:

- This product is light sensitive; exposure to daylight, UV light and artificial lighting should be kept to a minimum during storage and handling.
- Shake well before use.
- Recommended Post Print Processing:
  - Rinse the printed part using an approved cleaner to remove uncured resin
  - 100 seconds per side @ 100% intensity using Loctite CL36 cure chamber.
  - If desired, the clarity of the printed part can be improved by coating of the printed part with a thin layer of Loctite® 3D 3820™ prior to this UV exposure.

## Loctite Material Specification<sup>LMS</sup>

Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

## Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labelling.

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.**

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Centre or Customer Service Representative.

### Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$   
 $\text{kV/mm} \times 25.4 = \text{V/mil}$   
 $\text{mm} / 25.4 = \text{inches}$   
 $\mu\text{m} / 25.4 = \text{mil}$   
 $\text{N} \times 0.225 = \text{lb}$   
 $\text{N/mm} \times 5.71 = \text{lb/in}$   
 $\text{N/mm}^2 \times 145 = \text{psi}$   
 $\text{MPa} \times 145 = \text{psi}$   
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$   
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$   
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$   
 $\text{mPa}\cdot\text{s} = \text{cP}$

### Note

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada, Inc. the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office."

### Preliminary Technical Data

The performance data contained in this Preliminary Technical Data sheet is subject to final validation and may be adjusted/modified prior to final release.